



US009636846B1

(12) **United States Patent**
Squires

(10) **Patent No.:** **US 9,636,846 B1**
(45) **Date of Patent:** **May 2, 2017**

(54) **METHOD AND APPARATUS FOR
SIDEWARDS FLYING BED**

1,467,214 A * 9/1923 White D06F 37/36
366/219

(Continued)

(71) Applicants: **Arthur M. Squires Irrevocable Trust**,
Blacksburg, VA (US); **Steven**
Critchfield, Blacksburg, VA (US)

FOREIGN PATENT DOCUMENTS

FR 1565187 A * 4/1969 A47J 43/042

(72) Inventor: **Arthur M. Squires**, Blacksburg, VA
(US)

OTHER PUBLICATIONS

(73) Assignee: **Arthur M. Squires Irrevocable Trust**,
Blacksburg, VA (US)

Arthur M. Squires, Chemical process opportunities for vibrated
powders: 3. Provisional design for an experimental sideways flying
bed, Powder Technology, Jun. 6, 2007, pp. 56-62, vol. 175, Issue 2,
Department of Chemical Engineering, Virginia Polytechnic Institute
and State University, Blacksburg VA 24061-0211, USA.

(Continued)

(21) Appl. No.: **13/731,458**

Primary Examiner — Charles Cooley

(22) Filed: **Dec. 31, 2012**

Assistant Examiner — Marc C Howell

(74) *Attorney, Agent, or Firm* — James Creighton Wray;
Meera P. Narasimhan

Related U.S. Application Data

(60) Provisional application No. 61/581,301, filed on Dec.
29, 2011, provisional application No. 61/584,357,
filed on Jan. 9, 2012.

(51) **Int. Cl.**

B29B 11/04 (2006.01)

B01F 11/00 (2006.01)

(52) **U.S. Cl.**

CPC **B29B 11/04** (2013.01); **B01F 11/0002**
(2013.01)

(58) **Field of Classification Search**

CPC B01F 11/0002; B01F 11/0017; B01F
11/0097; B29B 11/04

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

891,788 A * 6/1908 Winans B60S 1/166
366/237

(57)

ABSTRACT

Granular matter placed in a vertical cylinder rotated back
and forth between limiting angles creates a sideways flying
bed. A spoke is connected at one between a vertical drive
shaft rotating the cylinder and a first hinge. A drive rod is
connected between the first hinge and a second hinge on a
rotating flywheel. Rotation of the flywheel causes the drive
shaft to rotate through an angle varying back and forth
between limiting angles. The cylinder's speed of rotation
varies. During most of the time centrifugal forces greater
than gravity act upon the granular material, causing the
material to form a layer on the inner wall of the cylinder. In
at least a portion of the recurring time intervals the accel-
eration and deceleration produce tangential forces greater
than the centrifugal forces acting upon the layer, causing the
granular material to fly sideways in a direction tangential to
the cylinder's circumference.

20 Claims, 5 Drawing Sheets

